

Electromobility in winter: Intelligent functions optimize range and charging performance

- **Preconditioning has a positive effect on range in winter**
- **e-tron route planner and range prognosis ensure planning security**
- **Conscious charging contributes to long high-voltage battery life**

Seat heating instead of a hot air blower, optimum tire pressure, parking in the garage, and selecting the efficiency mode: these and other factors determine how quickly the high-voltage battery is drained – or not. What can Audi customers do beyond the established tips to keep the high-voltage battery in their e-tron model working efficiently during the winter and to achieve optimal range?

1. Departure timer and preconditioning

Preconditioning climatizes the interior of the vehicle before departure to the desired temperature like with auxiliary heating. Apart from comfort, it is a function that also ensures more range. That is because during preconditioning with the departure timer, the energy that is needed to warm the battery in the winter is directed to the vehicle during charging via an external energy source – for instance, a home wallbox or a public charging point. The result: less heating power needs to be used while driving, which in turn benefits range. That is particularly relevant for bringing the battery to a comfortable temperature without pre-heating for energy-intensive short trips, when not much time is available.

2. e-tron route planner

In the purely electric models, the Audi e-tron route planner complements the Audi MMI's (MMI = Multi Media Interface) navigation features with about 30 pieces of detailed information and helps optimize the demands of e-mobility, especially when driving medium and longer distances: it calculates the fastest route, takes traffic and route data into account, considers the driver's driving style, calculates how long it will take to charge the vehicle, and includes it in the total driving time. Users are also shown basic information such as the charging power or charging connections and the plug type of the respective charging points. The system also shows whether charging stations are available or occupied. The Audi e-tron route planner gives preference to high-performance HPC charging stations (HPC = High Power Charging = ultra-fast charging) and, in the e-tron GT quattro models, activates battery preconditioning while driving.

The equipment, data and prices specified in this document refer to the model range offered in Germany. Subject to change without notice; errors and omissions excepted.

**The collective fuel/electric power consumption and emissions values of all models named and available on the German market can be found in the list provided at the end of this text.*

With an active e-tron route planner, the particular model always looks for the most efficient path to its destination. Additionally, the [range calculator](#) on the website shows the differences in range for the Audi e-tron* and the Audi e-tronSportback*- depending on external temperature, driving mode, rim size, and use of heating and air conditioning.

3. Charging at low temperature

The intelligent battery management system (BMS) communicates with the charging point or wallbox to optimize power for the gentlest possible AC charging. Charging is regulated automatically and the system ends the charge as soon as the battery is full or a predefined charge level of, for example, 80 percent has been reached. During the charging process, the BMS monitors the voltages in the individual cells and balances them as needed. Additionally, intelligent management engages battery heating. If the battery temperature falls below a certain limit, the BMS automatically reduces charging capacity in order to prioritize early aging of the battery. In all, slow charging has a positive effect on the lifespan of the battery. Additionally, it is advisable to charge as soon as possible after driving when the outside temperature is cold. That is because the battery is still warmed up and recharges more gently and quickly.

4. Range prognosis in the digital instrument panel

The range prognosis is derived from the high-voltage battery's charge level and the energy consumption forecast. This depends on several factors. Drive system consumption has the biggest effect on it. Convenience consumers and air conditioning have far less of an effect. For the projected range, Audi distinguishes between two scenarios: the active navigation route and inactive navigation. For the active navigation route, the projected consumption from the route profile (speed limits, green lights, differences in elevation) and current traffic information such as congestion as well as average energy consumption over the last 100 kilometers (62.1 miles). Additionally, anticipated convenience and climate consumption are assessed for the entire upcoming drive. When navigation is inactive, the average of the last 100 kilometers (62.1 miles) is applied to determine drive system consumption. Convenience and climate consumption are also assessed. By turning convenience consumers on and off via the range monitor, users can see their direct impact on the range prognosis.

5. High-voltage battery maintenance

Anyone who frequently makes short car trips should charge the battery to a maximum of 80 percent in order to save its capacity for longer ranges and to extend its lifespan. On the other hand, it is a good idea to avoid a long-lasting deep discharge when the charge level is below 20 percent. Anyone who frequently makes long car trips can charge up to 100 percent, but should then start driving immediately thereafter. Ideally, anyone who does not drive for longer than 12 hours should keep the charging level between 40 and 80 percent in the winter.

**The collective fuel/electric power consumption and emissions values of all models named and available on the German market can be found in the list provided at the end of this text.*

6. Geo-charging profile

This automated function in the Audi e-tron* records in the vehicle that drivers can activate or load previously configured charging profiles at particular locations.

Once location-based charging settings are set in the MMI and saved with the help of GPS coordinates, the charging settings and the timeframe for the charging process can be configured. Users can set charging profiles for several addresses.

7. Predictive preconditioning

In order to be able to use the Audi e-tron GT's* high HPC charging capacity of up to 270 kW, the high-voltage battery needs to be at a particular temperature. This is achieved by means of adapted preconditioning of the battery while driving. When an HPC charging station is entered as the destination in the e-tron route planner, an algorithm calculates the anticipated arrival time and deduces the necessary heating or cooling capacity from that in order to be able to access high charging capacity at the charging station right away for short idle time. If the customer wishes, the interior temperature is also correspondingly regulated.

8. Reducing driving resistance and convenience consumers

Smaller rim sizes, narrower tires, and the right air pressure can reduce the tires' rolling resistance in the winter. By contrast, roof boxes increase aerodynamic drag. Inside the car, steering wheel and seat heating save energy because they operate close to the body and consume less electricity. Switching to air-circulation mode reduces loss of range.

Product and Technology Communications

Benedikt Still

Spokesperson Audi e-tron, Audi e-tron S, Audi Q4 e-tron, Electric Engines, Battery Technology, Charging / Infrastructure

Phone: +49 841 89 89615

Mobile: +49 152 57718307

E-Mail: benedikt.still@audi.de

www.audi-mediacyenter.com

Product and Technology Communications

Christian Hartmann

Spokesperson Audi e-tronGT, Audi RS e-tron GT, Electric Mobility, Fuel Cell Technologies, Automated Driving

Phone: +49 841 89 45277

Mobile: +49 151 52844338

E-Mail: christian.hartmann@audi.de

www.audi-mediacyenter.com



The Audi Group is one of the most successful manufacturers of automobiles and motorcycles in the premium and luxury segments. The brands Audi, Ducati, Lamborghini and Bentley produce at 21 locations in 13 countries. Audi and its partners are present in more than 100 markets worldwide.

In 2021, the Audi Group delivered around 1.681 million cars from the Audi brand, 8,405 sports cars from the Lamborghini brand and 59,447 motorcycles from the Ducati brand to customers. In the 2021 fiscal year, AUDI AG achieved a total revenue of €53.1 billion and an operating profit before special items of €5.5 billion. More than 89,000 people all over the world work for the Audi Group, around 58,000 of them in Germany. With its attractive brands, new models, innovative mobility offerings and groundbreaking services, the group is systematically pursuing its path toward becoming a provider of sustainable, individual, premium mobility.

Fuel/electric power consumption and emissions values of the models named above:****Audi e-tron GT quattro**

Combined electric power consumption in kWh/100 km (62.1 mi): - (NEDC); 21.6–19.6 (WLTP); combined CO₂ emissions in g/km (g/mi): 0 (0)

Consumption and emissions values are only available according to WLTP and not according to NEFZ for this vehicle. Information on fuel consumption and CO₂ emissions in ranges are dependent on the chosen vehicle specification.

Audi e-tron Sportback

Combined electric power consumption in kWh/100 km (62.1 mi): 25.9–21.0 (WLTP); 24.0–20.9 (NEDC); combined CO₂ emissions in g/km (g/mi): 0 (0)

Audi e-tron

Combined electric power consumption in kWh/100 km (62.1 mi): 26.1–21.0 (WLTP); 24.3–20.9 (NEDC); combined CO₂ emissions in g/km (g/mi): 0 (0)

***The indicated consumption and emissions values were determined according to the legally specified measuring methods. The WLTP test cycle completely replaced the NEDC on January 1, 2022, which means that no NEDC figures are available for vehicles with new type approvals from after this date.*

The figures do not refer to a single, specific vehicle and are not part of the offering but are instead provided solely to allow comparisons of the different vehicle types. Additional equipment and accessories (add-on parts, different tire formats, etc.) may change relevant vehicle parameters, such as weight, rolling resistance and aerodynamics, and, in conjunction with weather and traffic conditions and individual driving style, may affect fuel consumption, electrical power consumption, CO₂ emissions and the performance figures for the vehicle. Due to the more realistic test conditions, the consumption and CO₂ emission values measured are in many cases higher than the values measured according to the NEDC. This may result in corresponding changes in vehicle taxation since September 1, 2018. Additional information about the differences between WLTP and NEDC is available at www.audi.de/wltp. Further information on official fuel consumption figures and the official specific CO₂ emissions of new passenger cars can be found in the “Guide on the fuel economy, CO₂ emissions and power consumption of all new passenger car models”, which is available free of charge at all sales dealerships and from DAT Deutsche Automobil Treuhand GmbH, Helmuth-Hirth-Str. 1, 73760 Ostfildern-Scharnhausen, Germany (www.dat.de).